

RETRACTOR

The PFI Retractor signature design can be used for an array of applications including transposing product from a wide to narrow pattern, pan loading, oven and freezer belt loading, or for simpler applications such as rejects or product dumps.

The unit is compatible with multiple belt choices including plastic modular, wire belting or conventional flat belting, with the possibility to accommodate belts up to 84" wide. Tight transfers on both the infeed and discharge are standard design features to ensure gentle product transfers and maintain product alignment. Integrated Servo Electrical Controls can be programmed for multiple products and desired strokes lengths at variable retraction speeds.

The unit features removable guarding to be easily accessible for cleaning and maintenance and also can be fitted with CIP bars to clean the surfaces of the belting.



DESIGN FEATURES

- TIGHT TRANSFERS
- SANITARY DESIGN
- LOW-MAINTENANCE
- QUIET OPERATION
- VARIOUS DESIGN OPTIONS



sales@pfi-global.com | www.pfi-global.com

Product shown are for illustrative purposes only and may display optional accessories or components. Please contact your sales representative for more information on product specifications. Precision Food Innovations (PFI) respectively reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice obligation. PFI and its respective logos are trademarks of Precision, Inc. in the US and/or other countries. Copyright ©2021 Precision, inc, all rights reserved. FPS 004-02 | 05/21

